



ROLLER



PANEL



ROMAN

Technical Data

Composition	30% polyester / 70% PVC
Width	3,000mm & 2,500mm
Weight	530gsm +/-5%
Thickness	0.75mm +/-5%
Opacity/Openness	≥ 6
Light Fastness	≥ 5 (Blue wool scale)
Coating	Polyester yarns with PVC coating
Flame Retardant	Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings
Cleaning	Wipe clean with warm soapy water and damp cloth



5 YEAR
WARRANTY



SCREEN



ECO
FRIENDLY



FLAME
RETARDANT



FR



STANDARD
100



Solar Properties

USA Standard Tested To Ashrae 74-73									
						Shading Coefficients (Sc)			
						3mm CL.	6mm CL.	9mm CL.	
	Ts	Rs	As	Tv/Vlt	O-F				
White	22	64	14	7	7	0.36	0.36	0.33	
Alabaster	20	61	19	6	6	0.38	0.38	0.34	
Off White	21	63	16	6	7	0.37	0.37	0.34	
Cotton	18	61	21	6	6	0.37	0.37	0.34	
Bone / Off White	17	57	26	6	6	0.40	0.40	0.35	
Taupe	12	41	47	7	7	0.50	0.50	0.40	
Grey	12	30	58	7	7	0.58	0.58	0.43	
Charcoal	6	5	89	6	6	0.73	0.73	0.51	
Bronze / Charcoal	6	7	87	6	6	0.72	0.72	0.50	
Black / Copper	7	8	85	7	7	0.71	0.71	0.50	
Black	7	4	89	6	6	0.74	0.74	0.51	
Platinum	7	10	83	11	7	0.72	0.68	0.50	

Ts Solar Transmittance	As Solar Absorbance	Tv Visual Light Transmission	G-Value % Solar Radiation through Fabric
Rs Solar Reflection	Tuv Ultraviolet Transmittance	O-F Openness Factor	G-Total % Solar Radiation through Blind and Window

